



SIGN UP'S Will be online only! And at the gate the day of demo. Follow prompts to sign up.

- **There will be a limit of 130 cars per night, so get there early to be sure to get in the show.**
- **All drivers will sign in and pay registration fee prior to inspection; there will be no refunds if you are disqualified.**
- ** All drivers will obey parking lot staff directions and rules or face immediate disqualification.**

THESE RULES ARE REVISED AS OF 2/9/17-MAKE SURE YOU ARE BUILDING OFF THESE RULES!

DRIVER ENTRY

1. Drivers must be 16 yrs of age, drivers age 16 & 17 must have parental permission in writing and have parent/guardian sign a form at registration.
2. Drivers not obeying the rules will be disqualified.
3. One person per car will be allowed-DRIVERS ONLY and there will be NO switching numbers.
4. For insurance reasons, no one under the age of 16 will be allowed in the pit area. Drivers must sign release form prior to working on or unloading cars.
5. No alcoholic beverages allowed in pits or on grounds. No one under the influence of alcohol or drugs will be allowed to run.
6. All cars are inspected; cars not meeting regulations will not be allowed to run. No money refunded.
7. Drivers must register their cars prior to inspection.
8. Driver can only run ONE car per night.

4-6-8 CYLINDER CARS

1. This derby will consist of heats of 4-6-8 cylinder cars (no limousines, hearses, convertibles, trucks, SUVs, vans, El Camino's or Rancheros)
2. There will be a 1st, 2nd, Best of Show (BOS) for each heat and will advance to the feature heat. 1st will receive \$300, 2nd \$250 and BOS \$150.
3. 8-cylinder Feature winner will receive \$1,500 2nd will receive \$500 Feature best of show will receive \$300.
4. 4-cylinder feature winner will receive \$1,500 2nd will receive \$500 and feature best of show will receive \$300.
5. Each night (Monday and Friday) two best painted cars will be picked winners will receive \$50 each
6. Sun roofs must be covered with METAL.
7. Any cars not pre-registered MUST have the driver door painted white. Roof signs will be permitted. A number will be issued at registration.
8. 4 cylinder cars must weigh less than 3000 pounds. If car weighs more than 3,000 pounds it will run with the bigger cars.

SAFETY RULES

1. Driver must have a **DOT approved helmet (see rule 3) w/shield and/or goggles.** Driver must have a working seatbelt.
2. Driver must wear long pants and long sleeved shirt **THIS WILL BE ENFORCED.**
3. Full face helmets ONLY, no snowcross/dirt bike style helmets unless visor is removed. Open face helmets will not be permitted.
4. Any driver losing consciousness during the event will be removed from heat and not allowed to return. If driver wants to run Friday after loss of consciousness they must provide a note from Doctor. Fire/EMS personal will have authority and backing of officials throughout event to ensure safety for all event participants and spectators.
5. Drivers door must be painted white.

DRIVING RULES

1. You **MUST** make contact every 60 seconds, you must give not receive.
2. **DO NOT** hit driver's door, if you see white **DO NOT** hit it. Doing so will lead to disqualification. Red flag means STOP-someone is hurt or there is a fire... **PAY ATTENTION!!**

CAR PREPERATION

1. Absolutely **NO** welding is allowed anywhere on the car unless noted below. No matter how small you will be sent home.
2. For frame and body rust hole repairs only cut out around the piece that is rotted out and repair it with the same size diameter and thickness of material and it can only overlap ½ inch. All hood and trunk latches as well as shocks and springs must be removed.
3. Remove all glass. Doors must be clean and free of glass, door handles and locks. Remove all lights, molding or anything else that may be knocked loose onto the track. Headliner and carpeting must be removed. All plastic and glass debris should be removed from the car. All plastic coverings and glass should be removed from the bumpers.
4. Two metal bars at least ¼ inch thick must be bolted on car from top of front fire wall to the front roof area. Holes in firewall must be covered with metal.
5. **FUEL TANKS:** The gas tank may be relocated and the original must be removed. If gas tanks are left in original position they must be chained with 2- 5/16 inch chains or secured with 2 steel straps only! (centered on the tank and tight). The chains may wrap around the tank and floor only (the chains **MAY NOT** wrap around the rear end.) The relocated tank may be moved to the inside of the car, forward of the rear wheels and behind the front seat. A metal firewall must be provided. **NO RATCHET, RUBBER STRAPS OR WIRE will be allowed.** If using a electric fuel pump either steel or high pressure fuel line must be used. No plastic cans or 5 gallon round metal gas cans will be allowed for gas tanks. All fuel tanks must be **FULLY** accessible for inspection and must have gas cap. You must cover the fuel tank.
All electric fuel pumps must have separate shut-off switch mounted to the dash **CLEARLY MARKED "FUEL". DECISIONS OF THE OFFICIALS WILL BE FINAL! Fuel lines must run under car or through fire wall.**
6. **REAR ENDS:** Rear ends may be locked or welded for posi-traction. Rear ends may be changed but must be a passenger car 5 lug or less and have the stock suspension for that make and model of the vehicle it is going into. Coil to leaf spring alterations will **NOT** be permitted.
7. All outside door seams may be welded with a maximum 3-inch-wide ¼ inch thick 12-inch-long metal plate or may be wired or chained shut with 5/16-inch chain, one per door.
8. A) Every car must have at least a backseat bar and if you do not run a four-point cage you must have a passenger seat. All backseat bars must have a 2-3-inch min/max ¼ inch thick square or round tubing **ONLY.** The backseat bar cannot exceed 5 inches from the driver's seat and cannot be

closer than 5 inches from the highest point of the floor board. It must also be below the top of your shoulders.

B) Four point cages and H-bars will be allowed, 2-3inch min/max ¼ inch thick square or round tubing only. Cage and backseat bar maybe welded or bolted with a 6 inch x 6 inch ¼ inch plate with 4 bolts in each plate. Dash bar must be no closer than 5 inches to the firewall, no closer than 5 inches to the highest point on the floorboard, and the back-seat bar cannot exceed 5 inches away from the driver's seat and cannot be closer than 5 inches to the highest point of the floor board. Side bars cannot exceed front dash and backseat bar. You may use one gusset per corner. Material must be the same as the cage material. They cannot exceed 12 inches in length. H-bar must be mounted off the back-seat bar and must be straight up and down extending over the roof and may be bolted to the roof in 2 spots only. You may use one gusset per side going from the cage to the H-bar 12-inch max. A tank protector maybe used only if a cage is being used. It must be mounted off, of the back-seat bar and cannot be wider than 24 inches and must be 5 inches away from any sheet metal. If a cage is not being used, you must have a backseat bar going side to side 2-3inch round or square tubing ¼ inch thick only. There will be no other material allowed for cage or back seat bars. You cannot run a center bar for cable shifters. If using a cable shifter, it must be mounted to the floor.

9. Hood and trunk must be chained with 5/16-inch chain or wired shut in 4 places only after inspection. Hood and trunk may be wired or chained through bumpers in two of these holes.
10. Engine and transmission swapping between manufactures is allowed. DO NOT strengthen frames or cross members with mounts. Motor mounts may be welded or bolted to cross member ONLY. One engine chain per side may be used wrapped once around frame only Do not weld links to frame or together. A factory transmission cross member for that make and model must be used but may be altered in the center for transmission mounting only (4" wide x 12" long x1/4 "thick max) **NO engine/transmission cradles or distributor protectors will be allowed.**
11. **TIRES:** Any DOT approved standard road tire will be allowed with NO aggressive tread on drive wheels and NO studded tires. All wheel weights must be removed from every tire!
12. **BUMPERS:** No special bumpers or any reinforcements will be allowed. Curved ends of the front bumpers may be cut off. You may re-bolt the bumper using same size bolts in existing holes or weld the bumper to the frame or mounts. Each bumper shock may be welded to the frame with only 6 inches of total weld per shock with **NO ADDED METAL.** Bumper shocks cannot be extended and must be in stock location. The bumper shock may be welded completely around the shock absorber to the bumper with no added metal. **IF your car didn't come with bumper shocks they cannot be added.** If you snub nose, you may weld a 5 inch x 5 inch x ¼ inch plate between the bumper and frame horn only. (This plate is only to be used when snub nosing only!)
13. Fender wells may be cut for clearance but **NOT** welded, rolled or re-attached for strength.
14. Shifting linkage may be hooked up directly to the transmission. Floor shifter may be used, but shifter handle must be safe
15. Electrical system hot wires may be installed.
16. There must be two 6 inch x 6 inch minimum openings in hood, one on either side for fire dept access. Hood holes may be cut out but no folding, rolling or reinforcing through the hood.
17. Exhaust may exit through the hood or go under car past firewall.
18. **BODY MOUNTS:** body mounts must remain in stock position. Body mounts may be replaced but must have a 1 ½ inch gap between the body and frame and cannot exceed 3 inches in diameter. You may use up to a 3-inch diameter ¼ inch thick washer and a 5/8-inch max for body bolts. Washers and spacers cannot be welded to the frame or body. **No folding, pinning, cold bending, or seam welding to the body or frame. No undercoating or painting on the frame**
19. If your car has anything on it that did not come from factory (distributor protectors, engine cradles, pulley protectors, rear-end braces etc.) it **MUST** be removed unless noted in rules.

20. Slide drive shafts will be allowed and steering columns may have **ONE** universal joint added.
21. **SUSPENSIONS:** Suspension must remain stock for that make and model. Coil springs may be tack welded or wired in place. Car may have a stiff suspension, but must remain within the max 22 inches from the ground to center of the front or rear bumper. Leaf spring cars must use factory size clamps, no more than 3 per side.
22. **RADIATORS:** Radiators or cooling devices must be in original position with **NO** reinforcements. No antifreeze will be allowed—WATER ONLY. Homemade boxes will be allowed with a max of 2ft x 2ft x 3 inches thick with a pressure relief cap and must be bolted or wired in **only**.
23. **BATTERIES:** Batteries and transmission coolers may be relocated inside car. Batteries must be secure and fuel and electric lines must run through fire wall and be protected. **NO milk crates or wooden boxes will be allowed as battery boxes. No ratchet straps may be used to secure batteries.** 2 pieces of threaded rod with a piece of metal across the top bolted to the floor. **Make sure that batteries have a rubber mat over them. MAX of two batteries per car.**
24. Unobserved items escaping detection during inspection does not make them legal. Non-conformance to the rules will be called illegal. At the end of the feature the winning cars will be re-inspected on the track before prize money and trophy are awarded. Any participant who violates the intent of The Delaware County Fair rules shall be considered to have engaged in unsportsmanlike conduct and will result in forfeiture of prize money and trophy and will also result in a 1 year suspension from the derby. Cars must conform to the rules listed above. Driver will have one chance to correct any issues found in primary inspection, after that the car will not be allowed to run.
- COMMON SENSE PREVAILS, THE DECISION OF THE OFFICIALS WILL BE FINAL!**
25. All decisions are final. No appeal process is implied or allowed. Officials have the right to alter the program at any time for necessary changes only. Even if your vehicle passes inspection prior to the derby, winner will be re-inspected, only driver allowed with car on re-inspection.